

08-01-00

A



**NON-PROVISIONAL
UTILITY PATENT APPLICATION
TRANSMITTAL - 37 CFR 1.53(b)**

☐ Duplicate
(check, if applicable)



Assistant Commissioner for Patents
BOX PATENT APPLICATION
Washington, DC 20231

Attorney Docket No. 9369-49 (T37-124487M/TH)
First Named Inventor: Hiroyuki MIYOSHI, et al.
Express Mail Label No. EL631602126US
Total Pages of Transmittal Form: 2

Transmitted herewith for filing is the non-provisional utility patent application entitled:

ELEVATOR APPARATUS

which is:

an ☒ Original; or

a ☐ Continuation, ☐ Divisional, or ☐ Continuation-in-part (CIP)
of prior Application No. /, filed .

☐ This non-provisional patent application is based on Provisional Patent Application
No. , filed .

Enclosed are:

- ☒ Specification (including Abstract) and claims: 16 pages.
- ☒ Newly executed Declaration (original).
- ☐ Copy of Declaration from prior application.
- ☐ Separate Power of Attorney (including 37 CFR 3.73(b) statement, if applicable).
- ☒ 2 sheets of drawings (formal) plus one copy.
- ☐ Microfiche computer program (Appendix).
- ☐ Nucleotide and/or Amino Acid Sequence Submission, including:
 - ☐ Computer readable copy ☐ Paper Copy ☐ Verified Statement.
- ☒ Under PTO-1595 cover sheet, an assignment of the invention.
- ☐ Certified copy(ies) of Application No(s) ., filed , is/are filed:
 - ☐ herewith or ☐ in prior application .
- ☐ Verified Statement Claiming Small Entity Status under 37 CFR 1.9 and 1.27.
 - ☐ was filed in the prior non-provisional application, and such status is still proper and desired (37 CFR 1.28(a));
 - ☐ is enclosed herewith; ☐ is no longer desired.
- ☐ Preliminary Amendment.
- ☒ Information Disclosure Statement, PTO-1449, and cited references.
- ☐ Other:

The following fees are being paid by:

☒ Our firm's check in the amount of \$690.00 is enclosed herewith; or

			SMALL ENTITY			LARGE ENTITY	
CLAIMS	NO. FILED	NO. EXTRA	BASIC FEE:			BASIC FEE:	
			\$345			\$690	
Total	6-20 =		X9	\$	OR	X18	\$
Independent	1- 3=		X39	\$	OR	X78	\$
Multiple Dependent Claims Present:			\$130	\$	OR	\$260	\$
			TOTAL	\$	OR	TOTAL	\$690.00

☒ This authorization to charge our firm's **Deposit Account No. 50-1017 (Billing No. 209369.0049)**.

- ☒ Any additional fees required under 37 C.F.R. § 1.16.
- ☒ Any additional fees required under 37 C.F.R. §1.17.
- ☒ In the event that a Petition for Extension of Time is required during the prosecution of this application, but not submitted, please charge any extension fee under 37 C.F.R. §1.136(a) to our Deposit Account noted above.
- ☒ Any additional fees/overpayments are authorized to be charged/credited to the above Deposit Account.

One additional copy of this paper is enclosed for accounting purposes.

CORRESPONDENCE ADDRESS:

July 31, 2000
(Date)

By: Martin G. Belisario
MARTIN G. BELISARIO
Registration No. 32,886
AKIN, GUMP, STRAUSS, HAUER & FELD, L.L.P.
One Commerce Square
2005 Market Street - Suite 2200
Philadelphia, PA 19103
Telephone: 215-965-1200
Direct Dial: 215-965-1303
Facsimile: 215-965-1210
E-Mail: mbelisario@akingump.com

☒ Customer Number or Bar Code Label: **000570**

MGB:jf
Enclosures

Elevator Apparatus

BACKGROUND OF THE INVENTION

The present invention relates to an elevator apparatus for moving an ascending and descending cage of an elevator upward and downward.

5 Recently, comparatively tall buildings relative to areas of grounds have been often built, because there are many cases where the grounds are limited in a city and the like. In such a tall building, an elevator is particularly required to ascend to high floors, and it is a problem how this elevator should be installed.

10 Although an elevator passage through which the ascending and descending cage of the elevator passes must be provided in a manner passing through respective floors, an actuating device for moving the elevator upward and downward can be installed at an optional position to some degree.

15 By the way, it is disclosed in Japanese Publication of unexamined Utility Model Application No. JP-A-59-40276U, for example, that the actuating device is provided below the elevator passage or at a side of the elevator passage at an intermediate part thereof. However, in such a structure, there has been a

20 problem that a first and a second rope pulleys are required to

be provided in an upper part of the elevator passage in order to transmit a power from the actuating device to the ascending and descending cage by way of the rope, which incurs a complexity of the structure and an increase of the cost.

5 In such a prior art, there has been another problem that in the structure in which the actuating device is provided below the elevator passage, an underground room having a size for accommodating the actuating device must be provided underground, and the cost will be further increased. Moreover, there has been
10 a further problem that in case a determined amount of space is provided above the elevator passage for a fear of an overrun of the ascending and descending cage, and rope pulleys are mounted in the upper part of the elevator passage, a ceiling of the top floor of the building will be higher.

15 On the other hand, Japanese Publication of unexamined Patent Application No. JP-A-58-16375 discloses that a machine room is provided at a side of the elevator passage on the top floor of the building to install the actuating device for the elevator in the machine room. However, such a structure has also a problem
20 that four deflecting sheaves are required above the ascending and descending cage, which incurs a complexity of the structure and an increase of the cost, similarly to the above described prior art. Moreover, the machine room having a large floor area for the

actuating device is required.

SUMMARY OF THE INVENTION

In view of the above described problems, it is an object of the invention to provide such an elevator apparatus that the cost for installing the elevator can be kept low, and that effective spaces are secured in the building.

In order to attain the above described object, there is provided, according to the invention, an elevator apparatus which comprises an actuating device including a sheave around which a rope engaged with an ascending and descending cage is wound, the sheave being adapted to rotate thereby to move the rope, and a driving section for rotating the sheave. The actuating device is installed in a machine room provided on a top floor of a building in which the ascending and descending cage is disposed. The machine room faces with an elevator passage for the ascending and descending cage.

According to the elevator apparatus of the invention, because the actuating device is installed in the machine room provided on the top floor of the building in which the ascending and descending cage is disposed, and the machine room faces with the elevator passage for the ascending and descending cage, the elevator apparatus can be constructed in a smaller space and composed of less components, without employing the rope pulleys

or the deflecting sheaves as in the prior art. Accordingly, the cost can be lowered. It is no more necessary that the ceiling of the top floor is set high unnecessarily. Further, because a height of the machine room is low, an effective space on the top floor of the building can be secured.

The present disclosure relates to the subject matter contained in Japanese patent application No. Hei. 11-219490 (filed on August 3, 1999), which is expressly incorporated herein by reference in its entirety.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a sectional side view of an actuating device for an elevator illustrating an embodiment according to the invention.

Fig. 2(a) is a view illustrating a state in which the actuating device 1 in Fig. 1 is disposed within a building 50, and Fig. 2(b) is a sectional view of the building 50 taken along a line IIB-IIB of Fig. 2(a).

DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereunder, a mode for carrying out the invention will be described referring to the drawings. Fig. 1 is a sectional side view of an actuating device 1 for an elevator illustrating an embodiment according to the invention.

As shown in Fig. 1, the actuating device 1 for the elevator

includes a motor assembly 10, a speed-reducer 20 adapted to reduce rotation speed of an input shaft 21 which is driven to rotate by means of the motor assembly 10 to transmit the rotation, and a brake assembly 30.

5 The motor assembly 10 has, in a housing 11 of the motor assembly 10, a coil 12, a stator 13 disposed adjacent to the coil 12, a rotor 14, a rotary disc 15 fixed to the rotor 14 and having its center part splinedly connected to the input shaft 21 to rotate therewith, and an encoder 16 for detecting number of the rotation
10 of the input shaft 21. The housing 11 is fixed to a support member 22 of the speed-reducer 20. The support member 22 is attached to a floor face of a machine room 58 of a building 50 which will be described later. The motor assembly 10 is so constructed that an electrical supply to the coil 12 is controlled by a control section
15 which is not shown, whereby a determined amount of torque is outputted.

As shown in Fig. 1, the speed-reducer 20 includes the input shaft 21 which is rotatably supported by means of a bearing 20a at a center part of the support member 22 (a rotation center of
20 the speed-reducer), a sheave 27 as an output rotary wheel which is rotatably supported by means of a pair of bearings 27a at an outer circumference of the support member 22, provided with grooves 28 on an outer periphery thereof to be wound by a rope

the rooftop 50a of the building 50, is shown an ascending and descending cage 52 which is hung by means of the rope 29 and movable upward and downward along a guide which is not shown.

One end of the rope 29 is attached to a fitting portion 51 provided on a lower face of the rooftop 50a. The rope 29 is wound around pulleys 52a, 52b provided on a lower face of the ascending and descending cage 52 to be directed upward, wound around the sheave 27 of the actuating device 1 to be directed downward, then, wound around a pulley 55 supporting the balance weight 56 to be directed upward, and finally attached to the fitting portion 51 at its other end.

As shown in Fig. 2(b), inside the building 50, is provided the elevator passage 59 extending in a vertical direction, and the ascending and descending cage 52 is movably disposed along the elevator passage 59. There is provided a machine room 58 on the top floor 57 of the building 50 facing with the elevator passage 59. The actuating device 1 is arranged in the machine room 58 in such a manner that the outer periphery of the sheave 27 is positioned above the rope 29 in a vertical direction. A control panel 2 including its control unit is also disposed adjacent to the actuating device 1. The machine room 58 has a height which is slightly higher than a height of an operator, that is, the height to such an extent that the operator can work inside the room without

bending his body. The height of the machine room 58 is smaller than a distance from a floor 57c to a ceiling 57d of the top floor 57. When the operator conducts an installation work or a maintenance work of the actuating device 1, he can ascend stairs 5 57a from the top floor 57 to a front of the machine room 58, and enter into the machine room 58 opening a door (not shown), thus providing a good access to the actuating device 1 and excellent workability. Since a door (not shown) of the ascending and descending cage 52 is adapted to be opened on the left hand or 10 right hand in Fig. 2(a), the actuating device 1 will not be an obstacle for going in and out of the elevator. Moreover, the operator can move from the ascending and descending cage 52 or from a ceiling of the ascending and descending cage 52 to the machine room 58.

15 Next, drive and control of the ascending and descending cage 52 of the elevator by the actuating device 1 according to this embodiment will be described. At first, the motor assembly 10 in Fig. 1 is actuated by a signal from the control section (not shown) to rotate the input shaft 21 together with the rotor 14. Through 20 the crank portion 21a of the input shaft 21, the external teethed gears 60 initiate eccentric swinging motions thus to cause the reduced rotation of the sheave 27 which has the internal teeth in mesh with the external teeth of the gears 60. Such reduction

motion has been known. This rotation of the sheave 27 actuates the rope 29 which is wound in the grooves 28 on the outer periphery of the sheave, thereby to move the ascending and descending cage of the elevator upward and downward. The rotation of the input shaft 21 is reduced through the speed-reducer 20 at a determined ratio to be transmitted to the sheave 27, which rotates at a constant rotation speed.

During the operation of the motor assembly 10, electric power is supplied to the electromagnet 40 of the brake assembly 30, and the electromagnet 40 attracts the armatures 36, 37. When the armatures 36, 37 are attracted and move in a direction of approaching to each other, the springs 38, 39 are pushed by the armatures 36, 37 to contract. Thus, the brake plates 32, 33 are released from the biasing forces of the springs 38, 39 and separated from the stationary walls 34, 35 to put the intermediate member 31 in a rotatable condition, thereby maintaining a state in which the input shaft 21 is not applied with the braking force.

On the other hand, when the electric supply from the non-shown control unit is suspended (including a power failure), the electromagnet 40 will no more attract the armatures 36, 37. Therefore, the brake plates 32, 33 are pressed against the stationary walls 34, 35 with strong biasing forces of the springs 38, 39 through the armatures 36, 37. On this occasion, since large

friction forces are exerted between the stationary walls 34, 35 and the brake plates 32, 33, a braking force can be applied to the input shaft 21 through the intermediate member 31 based on these friction forces. This causes the sheave 27 to stop the rotation.

According to the embodiment of the invention, as shown in Fig. 2(b), the ascending and descending cage 52 which has arrived at the top floor 57 (shown by an alternate long and short dash line) and the sheave 27 are laterally separated from each other, the ascending and descending cage 52 can approach to the ceiling 57d leaving the least allowable space for the overrun. Therefore, there is no need of providing the rope pulleys, the deflecting sheaves or the like in the upper part of the elevator passage 59, and so, the structure will be simplified and the overall height of the building 50 will not be unnecessarily increased. The allowable space for the overrun means a space formed between the ceiling 57d and an upper face of the ascending and descending cage 52 at its ordinary stopping position, in order to avoid a collision of the ascending and descending cage 52 with the ceiling 57d when it has overrun upward.

Because the output rotary wheel itself of the speed-reducer 20 constitutes the sheave 27 around which the rope 29 is wound, and at the same time, both the motor assembly 10 and the brake

assembly 30 are provided on a same plane which is at right angle with the input shaft 21, this actuating device can be designed to be thin in an axial direction of the input shaft 21 as compared with the conventional actuating device. As described, because the
5 actuating device 1 can be designed to be thin and compact, there is no need of providing the large-sized machine room on the top floor of the building 50 as in the conventional case, but the small machine room 58 will be sufficient to be provided. Therefore, a relatively large space S such as a storage can be provided below
10 the machine room 58 as shown in Fig. 2(b), and an effective use of the space on the top floor 57 can be attained.

Although the invention has been described referring to the embodiment hereinabove, the invention is not limited to the embodiment, but various modifications are possible within a scope
15 of technical concept of the invention. For example, the space S and the stairs 57a are provided in the above described embodiment, and the machine room 58 is defined between a floor above the space S and the ceiling 57d. However, the actuating device 1 may be installed on the floor 57c of the top floor 57, instead of providing
20 the space S and the stairs 57a, to define the machine room 58 between the floor 57c and the ceiling 57d of the top floor. Further, the structure as shown in this embodiment is simply one example of the actuating devices, and the actuating device is not limited

to the structure as shown in the described embodiment.

According to the elevator apparatus of the invention,
because the actuating device is installed in the machine room
provided on the top floor of the building in which the ascending
5 and descending cage is disposed, and the machine room faces with
the elevator passage for the ascending and descending cage, the
elevator apparatus can be constructed in a smaller space and
composed of less components, without employing the rope pulleys
or the deflecting sheaves as in the prior art. Accordingly, the
10 cost can be lowered. It is no more necessary that the ceiling of
the top floor is set high unnecessarily. Further, because the
height of the machine room is low, the effective space on the top
floor of the building can be secured.

WHAT IS CLAIMED IS:

1. An elevator apparatus comprising:

an actuating device including a sheave around which a rope engaged with an ascending and descending cage is wound, said sheave
5 being adapted to rotate thereby to move said rope with its rotation, and a driving section for rotating said sheave,

wherein said actuating device is installed in a machine room provided on a top floor of a building in which said ascending and descending cage is disposed, and said machine room faces with an
10 elevator passage for said cage.

2. The elevator apparatus according to claim 1, wherein said actuating device includes a support member, a speed-reducer mounted on a first side of said support member, a motor assembly mounted on a second side of said support member, and a brake
15 assembly supported on said second side of said support member, said second side being opposite from said first side.

3. The elevator apparatus according to claim 2, wherein said speed-reducer, said motor assembly and said brake assembly are arranged coaxially to one another.

20 4. The elevator apparatus according to claim 2, wherein said brake assembly is arranged radially inwardly of said motor assembly.

5. The elevator apparatus according to claim 2, wherein

an output shaft of said speed-reducer constitutes said sheave.

6. The elevator apparatus according to claim 2, wherein said support member is attached to a floor surface of said machine room.

ABSTRACT OF THE DISCLOSURE

An elevator apparatus has an actuating device including a sheave around which a rope engaged with an ascending and descending cage is wound and a driving section for rotating the sheave. The
5 sheave is adapted to rotate to move the rope with its rotation.

The actuating device is installed in a machine room provided on a top floor of a building in which the ascending and descending cage is disposed. The machine room faces with an elevator passage for the cage.

FIG. 1





FIG. 2



Attorney Docket No.
9369-49US
(T37-124487M/TH)

DECLARATION AND POWER OF ATTORNEY
(Original Application)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ELEVATOR APPARATUS
the specification of which is attached hereto and/or was filed on July 31, 2000 as
Application No. _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to herein.

I acknowledge the duty to disclose information which is material to patentability in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

FOREIGN PRIORITY APPLICATION(S)

			Priority Claimed
<u>P.Hei.11-219490</u>	<u>Japan</u>	<u>3/August/1999</u>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/month/year filed)	
<u> </u>	<u> </u>	<u> </u>	<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/month/year filed)	

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional patent application(s) listed below and have also identified below any United States provisional patent application(s) having a filing date before that of the application on which priority is claimed:

PROVISIONAL PRIORITY PATENT APPLICATION(S)

<hr/>	<hr/>	<u>Priority Claimed</u> <input type="checkbox"/> Yes <input type="checkbox"/> No
(Application No.)	(Filing Date)	
<hr/>	<hr/>	<input type="checkbox"/> Yes <input type="checkbox"/> No
(Application No.)	(Filing Date)	

And I hereby appoint the registered attorneys and agents associated with **AKIN, GUMP, STRAUSS, HAUER & FELD, L.L.P.**, Customer No. 000570, as my attorneys or agents with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Address all correspondence to **Customer No. 000570, namely, AKIN, GUMP, STRAUSS, HAUER & FELD, L.L.P.**, One Commerce Square, 2005 Market Street, Suite 2200, Philadelphia, Pennsylvania 19103. Please direct all communications and telephone calls to Martin G. Belisario (Direct Dial 1303) at 215-965-1210

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of sole
inventor, if any Hiroyuki MIYOSHI

Inventor's Signature Hiroyuki Miyoshi

Date July 21, 2000

Residence Mie, Japan

Citizenship Japan

Post Office Address c/o Tsu Plant of TEIJIN SEIKI CO., LTD.
594, Ichimachida, Katada-cho, Tsu-shi, Mie, Japan

Full name of second joint
inventor, if any Takashi KUGA

Inventor's Signature Takashi Kuga

Date July 21, 2000

Residence Mie, Japan

Citizenship Japan

Post Office Address c/o Tsu Plant of TEIJIN SEIKI CO., LTD.
594, Ichimachida, Katada-cho, Tsu-shi, Mie, Japan

Full name of third joint
inventor, if any _____

Inventor's Signature _____

Date _____

Residence _____

Citizenship _____

Post Office Address _____